



The Public Health and Safety Organization

NSF Product and Service Listings

These NSF Official Listings are current as of **Thursday, December 19, 2019** at 12:15 a.m. Eastern Time. Please [contact NSF](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information: <http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=0C850&Standard=061&>

NSF/ANSI/CAN 61 Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of [Abbreviations used in these Listings](#). Click here for the definitions of [Water Contact Temperatures denoted in these Listings](#).

Endress + Hauser Flowtec AG

Kaegenstrasse 7
Reinach BL 1
CH-4153
Switzerland
41 61 7156111

Facility : Greenwood, IN

Mechanical Devices

| Trade Designation | Size | Water Contact Temp | Water Contact Material |
|-------------------------|------------|--------------------|------------------------|
| Water Meters [G] | | | |
| Promag D[1] [5] | 1" - 6" | C. HOT | MLTPL |
| Promag L[2] [5] | 2" - 3" | CLD 23 | MLTPL |
| Promag L[2] [5] | 4" - 90" | D. HOT | MLTPL |
| Promag L[3] [5] | 1" - 80" | CLD 23 | MLTPL |
| Promag L[4] [5] | 1/2" - 24" | C. HOT | MLTPL |
| Promag P[4] [5] | 1/2" - 24" | C. HOT | MLTPL |
| Promag S[2] [5] | 2" - 3" | CLD 23 | MLTPL |
| Promag S[2] [5] | 4" - 90" | D. HOT | MLTPL |
| Promag S[3] [5] | 1" - 80" | CLD 23 | MLTPL |
| Promag S[4] [5] | 1/2" - 24" | C. HOT | MLTPL |
| Promag W[2] [5] | 2" - 3" | CLD 23 | MLTPL |
| Promag W[2] [5] | 4" - 90" | D. HOT | MLTPL |
| Promag W[3] [5] | 1" - 80" | CLD 23 | MLTPL |
| Promag W[4] [5] | 1/2" - 24" | C. HOT | MLTPL |

- [1] Liner: Polyamide
Electrode Options: 1.4435/316L SS
- [2] Liner: Hard Rubber
Electrode Options: 1.4435/316L SS, Alloy C-22
- [3] Liner: Polyurethane or Hard Rubber
Electrode Options: 1.4435/316L SS, Alloy C-22
- [4] Liner: PTFE
Electrode Options: 1.4435/316L SS, Alloy C-22
- [5] Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.
- [G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Facility : Suzhou, China**Mechanical Devices**

| Trade Designation | Size | Water Contact Temp | Water Contact Material |
|--------------------------|-------------|---------------------------|-------------------------------|
| Water Meters [G] | | | |
| Promag L[3] [4] | 2" - 120" | CLD 23 | MLTPL |
| Promag S[3] [4] | 2" - 120" | CLD 23 | MLTPL |
| Promag W[2] [3] | 1" - 80" | CLD 23 | MLTPL |
| Promag W[3] [4] | 2" - 120" | CLD 23 | MLTPL |
| Promag L[2] [3] | 1" - 80" | CLD 23 | MLTPL |
| Promag D[1] [3] | 1" - 6" | C. HOT | MLTPL |
| Promag S[2] [3] | 1" - 80" | CLD 23 | MLTPL |

- [1] Liner: Polyamide
Electrode Options: 1.4435/316L SS
- [2] Liner: Polyurethane or Hard Rubber
Electrode Options: 1.4435/316L SS, Alloy C-22
- [3] Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.
- [4] Liner: Hard Rubber
Electrode Options: 1.4435/316L SS, Alloy C-22
- [G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Facility : Cernay, France**Mechanical Devices**

| Trade Designation | Size | Water Contact Temp | Water Contact Material |
|-------------------------|------------|--------------------|------------------------|
| Water Meters [G] | | | |
| Promag C[2] [5] | 2" - 12" | CLD 23 | MLTPL |
| Promag D[1] [5] | 1" - 6" | C. HOT | MLTPL |
| Promag L[2] [5] | 2" - 3" | CLD 23 | MLTPL |
| Promag L[2] [5] | 4" - 90" | D. HOT | MLTPL |
| Promag L[3] [5] | 1" - 80" | CLD 23 | MLTPL |
| Promag L[4] [5] | 1/2" - 24" | C. HOT | MLTPL |
| Promag P[4] [5] | 1/2" - 24" | C. HOT | MLTPL |
| Promag S[2] [5] | 2" - 3" | CLD 23 | MLTPL |
| Promag S[2] [5] | 4" - 90" | D. HOT | MLTPL |
| Promag S[3] [5] | 1" - 80" | CLD 23 | MLTPL |
| Promag S[4] [5] | 1/2" - 24" | C. HOT | MLTPL |
| Promag W[2] [5] | 2" - 3" | CLD 23 | MLTPL |
| Promag W[2] [5] | 4" - 90" | D. HOT | MLTPL |
| Promag W[3] [5] | 1" - 80" | CLD 23 | MLTPL |
| Promag W[4] [5] | 1/2" - 24" | C. HOT | MLTPL |

[1] Liner: Polyamide

Electrode Options: 1.4435/316L SS

[2] Liner: Hard Rubber

Electrode Options: 1.4435/316L SS, Alloy C-22

[3] Liner: Polyurethane or Hard Rubber

Electrode Options: 1.4435/316L SS, Alloy C-22

[4] Liner: PTFE

Electrode Options: 1.4435/316L SS, Alloy C-22

[5] Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Facility : Aurangabad, India

Mechanical Devices

| Trade Designation | Size | Water Contact Temp | Water Contact Material |
|-------------------------|----------|--------------------|------------------------|
| Water Meters [G] | | | |
| Promag D[1] [3] | 1" - 6" | C. HOT | MLTPL |
| Promag L[3] | 4" - 90" | D. HOT | MLTPL |
| Promag L[2] [3] | 1" - 80" | CLD 23 | MLTPL |
| Promag S[2] [3] | 1" - 80" | CLD 23 | MLTPL |
| Promag S[3] | 4" - 90" | D. HOT | MLTPL |
| Promag W[2] [3] | 1" - 80" | CLD 23 | MLTPL |

Promag W[3]

4" - 90"

D. HOT

MLTPL

[1] Liner: Polyamide

Electrode Options: 1.4435/316L SS

[2] Liner: Polyurethane or Hard Rubber

Electrode Options: 1.4435/316L SS, Alloy C-22

[3] Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Number of matching Manufacturers is 1

Number of matching Products is 43

Processing time was 0 seconds