

SECTION 1: Identification of the substance or mixture and of the supplier**1.1 Product identifier****Trade name:** Aktivator für Filtermembrane (CAT411,430)**Synonym:** *Activator for membrane filter (CAT411,430)***Article number:** 71000460**1.2 Relevant identified uses of the substance or mixture and uses advised against***No further relevant information available.***Application of the substance / the mixture** *Laboratory chemicals***1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:***Endress+Hauser
Conducta GmbH+Co. KG
Dieselstraße 24
D-70839 Gerlingen***Further information obtainable from:***Phone: +49 (0)7156 209-10117
E-Mail: MSDS.PCC@endress.com***1.4 Emergency telephone number:** 0064 800 764 766**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008***flame**Flam. Liq. 2 H225 Highly flammable liquid and vapour.**Eye Irrit. 2 H319 Causes serious eye irritation.**STOT SE 3 H336 May cause drowsiness or dizziness.***Classification according to Directive 67/548/EEC or Directive 1999/45/EC***Xi; Irritant**R36: Irritating to eyes.**F; Highly flammable**R11: Highly flammable.**R67: Vapours may cause drowsiness and dizziness.***Information concerning particular hazards for human and environment:***The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.**Has a narcotising effect.***Classification system:***The classification is according to the latest editions of the EU-lists, and extended by company and literature data.***2.2 Label elements****Labelling according to EU guidelines:***The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.*

(Contd. on page 2)

Trade name: Aktivator für Filtermembrane (CAT411,430)

(Contd. of page 1)

Code letter and hazard designation of product:



Xi Irritant
F Highly flammable

Risk phrases:

11 *Highly flammable.*
36 *Irritating to eyes.*
67 *Vapours may cause drowsiness and dizziness.*

Safety phrases:

7/9 *Keep container tightly closed and in a well-ventilated place.*
16 *Keep away from sources of ignition - No smoking.*
23 *Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).*
24/25 *Avoid contact with skin and eyes.*
60 *This material and its container must be disposed of as hazardous waste.*

2.3 Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

Results of PBT and vPvB assessment

PBT: *Not applicable.*
vPvB: *Not applicable.*

SECTION 3: Composition/Information on ingredients

3.2 Mixtures

Description: *Mixture of substances listed below with nonhazardous additions.*

Dangerous components:

CAS: 67-63-0	propan-2-ol	30-50%
EINECS: 200-661-7	Xi R36; F R11 R67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	

Additional information: *For the wording of the listed hazard phrases refer to section 16.*

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: *Immediately remove any clothing soiled by the product.*

After inhalation: *Supply fresh air; consult doctor in case of complaints.*

After skin contact: *Immediately rinse with water.*

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: *If symptoms persist consult doctor.*

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

*** SECTION 5: Fire fighting measures**

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: *no further information*

(Contd. on page 3)

Trade name: Aktivator für Filtermembrane (CAT411,430)

(Contd. of page 2)

5.2 Special hazards arising from the substance or mixture *No further relevant information available.*

5.3 Advice for firefighters *No further relevant information available.*

Protective equipment: *No special measures required.*

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: *Store in a cool location.*

Information about storage in one common storage facility: *Not required.*

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 67-63-0 propan-2-ol

WES (New Zealand) Short-term value: 1230 mg/m³, 500 ppm

Long-term value: 983 mg/m³, 400 ppm

Additional information: *The lists valid during the making were used as basis.*

8.2 Exposure controls

Appropriate engineering controls *No further data; see item 7.*

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

(Contd. on page 4)

Trade name: Aktivator für Filtermembrane (CAT411,430)

(Contd. of page 3)

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Protective gloves

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information**

Physical state

Fluid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

82 °C

Flammability

Not applicable.

Lower and upper explosion limit

Lower:

2 Vol %

Upper:

12 Vol %

Flash point:

< 23 °C

Ignition temperature:

425 °C

Decomposition temperature:

Not determined.

pH

Not determined.

Viscosity:

Kinematic viscosity

Not determined.

Dynamic:

Not determined.

Solubility

water:

Fully miscible.

Partition coefficient n-octanol/water (log value)

Not determined.

(Contd. on page 5)

Trade name: Aktivator für Filtermembrane (CAT411,430)

(Contd. of page 4)

Vapour pressure at 20 °C:	43 hPa
Density and/or relative density	
Density at 20 °C:	0.892 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Solvent content:	
Organic solvents:	50.0 %
Water:	50.0 %
Solids content:	0.0 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity**10.1 Reactivity** No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.**10.4 Conditions to avoid** No further relevant information available.**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 6)

Trade name: Aktivator für Filtermembrane (CAT411,430)

(Contd. of page 5)

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity****LD/LC50 values relevant for classification:****CAS: 67-63-0 propan-2-ol**

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rbt)
Inhalative	LC50/4 h	30 mg/l (rat)

Serious eye damage/irritation Causes serious eye irritation.**STOT-single exposure** May cause drowsiness or dizziness.**11.2 Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects**Additional ecological information:****General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**Recommended cleansing agents:** Water, if necessary together with cleansing agents.*** SECTION 14: Transport information****14.1 UN number or ID number**

IMDG, IATA

UN1219

14.2 UN proper shipping name

ADR

UN1219 ISOPROPANOL (ISOPROPYL ALCOHOL) solution

IMDG

ISOPROPANOL (ISOPROPYL ALCOHOL) solution

IATA

Isopropanol (isopropyl alcohol) solution

(Contd. on page 7)

Trade name: Aktivator für Filtermembrane (CAT411,430)

(Contd. of page 6)

14.3 Transport hazard class(es)

ADR



Class 3 (F1) Flammable liquids.
Label 3

IMDG, IATA



Class 3 Flammable liquids.
Label 3

14.4 Packing group

ADR, IMDG, IATA

II

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user

Warning: Flammable liquids.

Hazard identification number (Kemler code):

33

EMS Number:

F-E,S-D

Stowage Category

B

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 1L

Transport category 2

Tunnel restriction code D/E

IMDG

Limited quantities (LQ) 1L

Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation":

UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) SOLUTION, 3, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

New Zealand Inventory of Chemicals

All ingredients are listed.

HSNO Approval numbers

CAS: 67-63-0 | propan-2-ol

HSR001180

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

National regulations:

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 8)

Trade name: Aktivator für Filtermembrane (CAT411,430)

(Contd. of page 7)

15.2 Chemical safety assessment: *A Chemical Safety Assessment has not been carried out.***SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

16.1 Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

R11 Highly flammable.

R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

16.3 Recommended restriction of use

Department issuing SDS: PCC-TWR

Contact: *MSDS.pcc@endress.com*

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

*** Data compared to the previous version altered.**