

SECTION 1: Identification

Product identifier

Trade name: KIT CAT411 Ersatzmembranen, 2 Stück

Synonym: *KIT CAT411 reserve membrane, 2 pcs*

Article number: 51511288

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture *Laboratory chemicals*

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

*Endress+Hauser
Conducta GmbH+Co. KG
Dieselstraße 24
D-70839 Gerlingen*

Further information obtainable from:

*Phone: +49 (0)7156 209-10117
E-Mail: MSDS.PCC@endress.com*

*Regional representation:
Endress+Hauser Australia Pty Ltd
16 Giffnock Avenue
Macquarie Park, NSW 2113
Australia*

*Phone: 1300 363 707
Phone: +61 2 8877 7000*

Emergency telephone number: *Poison Hotline: 13 11 26*

SECTION 2: Hazard(s) Identification

Classification of the substance or mixture



flame

Flam. Liq. 2

H225 Highly flammable liquid and vapour.



Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

Label elements

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS02 GHS07

Signal word *Danger*

Hazard statements

*Highly flammable liquid and vapour.
Causes serious eye irritation.*

Trade name: KIT CAT411 Ersatzmembranen, 2 Stück

(Contd. of page 1)

*May cause drowsiness or dizziness.***Precautionary statements***Keep away from heat/sparks/open flames/hot surfaces. No smoking.**IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***Other hazards***The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.***Results of PBT and vPvB assessment****PBT:** *Not applicable.***vPvB:** *Not applicable.***SECTION 3: Composition and Information on Ingredients****Mixtures****Description:** *Mixture of substances listed below with nonhazardous additions.***Dangerous components:**

CAS: 67-63-0	propan-2-ol	30-50%
EINECS: 200-661-7	⚠ Flam. Liq. 2, H225; ⚠ Serious eye damage/irritation – Category 2A, H319; STOT SE 3, H336	

Additional information: *For the wording of the listed hazard phrases refer to section 16.***SECTION 4: First Aid Measures****Description of first aid measures****General information:** *Immediately remove any clothing soiled by the product.***After inhalation:** *Supply fresh air; consult doctor in case of complaints.***After skin contact:** *Immediately rinse with water.***After eye contact:***Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.***After swallowing:** *If symptoms persist consult doctor.***Most important symptoms and effects, both acute and delayed***No further relevant information available.***Indication of any immediate medical attention and special treatment needed***No further relevant information available.***SECTION 5: Fire Fighting Measures****Extinguishing media****Suitable extinguishing agents:***CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.***For safety reasons unsuitable extinguishing agents:** *no further information***Special hazards arising from the substance or mixture** *No further relevant information available.***Advice for firefighters** *No further relevant information available.***Protective equipment:** *No special measures required.***SECTION 6: Accidental Release Measures****Personal precautions, protective equipment and emergency procedures***Wear protective equipment. Keep unprotected persons away.*

(Contd. on page 3)

Trade name: KIT CAT411 Ersatzmembranen, 2 Stück

(Contd. of page 2)

Wear protective clothing.

Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and Storage

Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: *Store in a cool location.*

Information about storage in one common storage facility: *Not required.*

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

Specific end use(s) *No further relevant information available.*

SECTION 8: Exposure controls and personal protection

Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 67-63-0 propan-2-ol

WES (Australia) Short-term value: 1230 mg/m³, 500 ppm

Long-term value: 983 mg/m³, 400 ppm

Additional information: *The lists valid during the making were used as basis.*

Exposure controls

Appropriate engineering controls *No further data; see section 7.*

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 4)

Trade name: KIT CAT411 Ersatzmembranen, 2 Stück

(Contd. of page 3)

Hand protection



Protective gloves

To avoid skin problems reduce the wearing of gloves to the required minimum.
Only use chemical-protective gloves with CE-labelling of category III.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and Chemical Properties

Information on basic physical and chemical properties

General Information

Physical state

Fluid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

82 °C

Flammability

Highly flammable.

Lower and upper explosion limit

Lower:

2 Vol %

Upper:

12 Vol %

Flash point:

< 23 °C

Auto-ignition temperature:

425 °C

Decomposition temperature:

Not determined.

pH

Not determined.

Viscosity:

Kinematic viscosity

Not determined.

Kinematic viscosity

Dynamic:

Not determined.

Solubility

water:

Fully miscible.

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C:

43 hPa

Vapour pressure:

Density and/or relative density

Density at 20 °C:

0.892 g/cm³

Relative density

Not determined.

(Contd. on page 5)

Trade name: KIT CAT411 Ersatzmembranen, 2 Stück

(Contd. of page 4)

Vapour density	<i>Not determined.</i>
Other information	
Appearance:	
Form:	<i>Fluid</i>
Important information on protection of health and environment, and on safety.	
Ignition temperature:	<i>Product is not selfigniting.</i>
Explosive properties:	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</i>
Solvent content:	
Organic solvents:	<i>50.0 %</i>
Water:	<i>50.0 %</i>
Solids content:	<i>0.0 %</i>
Change in condition	
Evaporation rate	<i>Not determined.</i>
Information with regard to physical hazard classes	
Explosives	<i>Void</i>
Flammable gases	<i>Void</i>
Aerosols	<i>Void</i>
Oxidising gases	<i>Void</i>
Gases under pressure	<i>Void</i>
Flammable liquids	<i>Highly flammable liquid and vapour.</i>
Flammable solids	<i>Void</i>
Self-reactive substances and mixtures	<i>Void</i>
Pyrophoric liquids	<i>Void</i>
Pyrophoric solids	<i>Void</i>
Self-heating substances and mixtures	<i>Void</i>
Substances and mixtures, which emit flammable gases in contact with water	<i>Void</i>
Oxidising liquids	<i>Void</i>
Oxidising solids	<i>Void</i>
Organic peroxides	<i>Void</i>
Corrosive to metals	<i>Void</i>
Desensitised explosives	<i>Void</i>

SECTION 10: Stability and Reactivity

Reactivity *No further relevant information available.*

Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions *No dangerous reactions known.*

Conditions to avoid *No further relevant information available.*

Incompatible materials: *No further relevant information available.*

Hazardous decomposition products: *No dangerous decomposition products known.*

SECTION 11: Toxicological Information

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity *Based on available data, the classification criteria are not met.*

LD/LC50 values relevant for classification:

CAS: 67-63-0 propan-2-ol

<i>Oral</i>	<i>LD50</i>	<i>5,045 mg/kg (rat)</i>
<i>Dermal</i>	<i>LD50</i>	<i>12,800 mg/kg (rbt)</i>

(Contd. on page 6)

Trade name: KIT CAT411 Ersatzmembranen, 2 Stück

(Contd. of page 5)

Inhalative | LC50/4 h | 30 mg/l (rat)

Serious eye damage/irritation Causes serious eye irritation.**STOT-single exposure** May cause drowsiness or dizziness.**Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological Information**Toxicity****Aquatic toxicity:** No further relevant information available.**Persistence and degradability** No further relevant information available.**Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

Other adverse effects**Additional ecological information:****General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations**Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**Recommended cleansing agents:** Water, if necessary together with cleansing agents.**SECTION 14: Transport information****UN number or ID number****IMDG, IATA**

UN1219

UN proper shipping name**ADG**

UN1219 ISOPROPANOL (ISOPROPYL ALCOHOL) solution

IMDG**IATA**

ISOPROPANOL (ISOPROPYL ALCOHOL) solution

Transport hazard class(es)

Isopropanol (isopropyl alcohol) solution

ADG**Class**

3 (F1) Flammable liquids.

(Contd. on page 7)

— AUS —

Trade name: KIT CAT411 Ersatzmembranen, 2 Stück

(Contd. of page 6)

Label 3

IMDG, IATA



Class 3 Flammable liquids.
Label 3
Packing group
ADG, IMDG, IATA II
Environmental hazards: Not applicable.
Special precautions for user Warning: Flammable liquids.
Hazard identification number (Kemler code): 33
EMS Number: F-E,S-D
Stowage Category B
Maritime transport in bulk according to IMO instruments Not applicable.

Transport/Additional information:

ADG
Limited quantities (LQ) 1L
Transport category 2
Tunnel restriction code D/E

IMDG

Limited quantities (LQ) 1L
Excepted quantities (EQ) Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation": UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) SOLUTION, 3, II

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory of Industrial Chemicals

All ingredients are listed.

Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

Australia: Priority Existing Chemicals

None of the ingredients is listed.

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS02 GHS07

Signal word *Danger*

Hazard statements

Highly flammable liquid and vapour.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.

(Contd. on page 8)

Trade name: KIT CAT411 Ersatzmembranen, 2 Stück

(Contd. of page 7)

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

National regulations:

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: PCC-TWR

Contact: MSDS.pcc@endress.com

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.