

This is to certify:

TYPE APPROVAL CERTIFICATE

Certificate no.: **TAA00002KV**Revision No: 3

that the Temperature Transmitter		
with type designation(s) TM311		
issued to Endress+Hauser Wetzer GmbH+Co. KG Nesselwang, Germany		
is found to comply with DNV rules for classification – Ships, offshore units, and high speed and light craft		
Application:		
Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.		
Location classes:		
Temperature Humidity Vibration EMC Enclosure	D B B C	
Issued at Hamburg on 2025-02-03		
This Certificate is valid until 2030-02-02. DNV local unit: Augsburg		
Approval Engineer: Dariusz Lesniewski		

Form code: TA 251 Revision: 2024-11 www.dnv.com Page 1 of 2

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.



Job ID: 262.1-032118-3 Certificate no.: **TAA00002KV**

Revision No:

Product description

TM311 compact temperature transmitter Temperature measuring range: -50°C to +200°C

Output signal: 4...20mA / IO-Link (type-approved power supply required)

Accuracy: ±1% FS (analogue) Power supply: 24V DC

Electrical connection: M12x1 (plug male)

Tube diameter: 3mm or 6mm (for installation in thermowell)

Process connection (male thread): ½" NPT, ¼" NPT, G ½", G ¼", M 14x1.5, M 18x1.5 or without process connection

Max. insertion length: 200mm Degree of protection: IP66/IP67/IP69

Application/Limitation

The device must be operated with a type-approved transmitter power supply

Approval conditions

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV rules for classification of ships Pt.4 Ch.9 Control and monitoring systems.

Type Approval documentation

Test report: E+H QUD_F2048_TM311_climate_DNV_GL_EN_V0100.docx, 2019-08-30 Test report: E+H QUD F2048 TM311 high voltage DNV GL EN V0100.docx, 2019-08-30 Test report: E+H QUD_F2048_TM311_vibration_DNV_GL_EN_V0100.docx, 2019-08-30

Test reports: E+H 970007199, E+H 970007198, E+H 970007200, 2019-03-25

Test report: BV CPSG 19TUR043_EN61326-1_0, 2019-07-30 Document: QUD_F2048_Performance test EUT_EN_V0100.doc, 2019-05-14

E+H Certificate-No. P703EF044E3 2020, 2020-02-27 E+H Certificate-No. P703F1044E3 2020, 2020-02-27 Operating Instructions: BA01952T/09/EN/04.22 Technical Information: TI01439T/09/EN/04.22

Drawings: Circuit Diagrams, PCB Assembly Plans, Assembly Drawing Type approval assessment report issued at Augsburg on 2025-01-14

Tests carried out

Applicable tests according to class guideline DNV-CG-0339, August 2021.

Marking of product

The products to be marked with:

- manufacturer name
- model name
- serial number
- power supply ratings

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE

Form code: TA 251 Revision: 2024-11 www.dnv.com Page 2 of 2