in accordance with SANS

Printing date 18.03.2022

# Endress+Hauser

People for Process Automation Version 3 (replaces version 2)

Revision: 18.03.2022

# **SECTION 1: Identification of the substance or mixture and of the supplier**

### Product identifier

Trade name: <u>Aktivator für Filtermembrane (CAT411,430)</u> Synonym: Activator for membrane filter (CAT411,430)

Article number: 71000460

Recommended use of the chemical and restrictions on use No further relevant information available.

Application of the substance / the mixture Laboratory chemicals

Supplier's details Manufacturer/Supplier: Endress+Hauser Conducta GmbH+Co. KG Dieselstraße 24 D-70839 Gerlingen

Further information obtainable from: Phone: +49 (0)7156 209-10117 E-Mail: MSDS.PCC@endress.com

Emergency phone number +27 (0)861 555 777

# **SECTION 2: Hazard identification**

### Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



*Eye Irrit.* 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

#### GHS label elements GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS). Hazard pictograms



Signal word Danger

Hazard-determining components of labelling: propan-2-ol Hazard statements Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. May cause drowsiness or dizziness. Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

in accordance with SANS

Printing date 18.03.2022

Revision: 18.03.2022

### Trade name: Aktivator für Filtermembrane (CAT411,430)

(Contd. of page 1)

Page 2/8

Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes. Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

# **SECTION 3: Composition or information on ingredients**

### Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 67-63-0	propan-2-ol	30-50%
EINECS: 200-661-7	🚸 Flam. Liq. 2, H225; 🐠 Eye Irrit. 2, H319; STOT SE 3, H336	
Additional information: For the wording of the listed hazard phrases refer to section 16.		

### **SECTION 4: First-aid measures**

### Description of necessary first-aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately rinse with water.

### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor. Most important symptoms or effects, acute and delayed No further relevant information available.

Indication of immediate medical attention and special treatment needed, if necessary No further relevant information available.

# **SECTION 5: Fire-fighting measures**

Suitable extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. For safety reasons unsuitable extinguishing agents: no further information Specific hazards arising from the chemical No further relevant information available. Special protective actions for fire fighters No further relevant information available. Protective equipment: No special measures required.

# **SECTION 6: Accidental release measures**

Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Wear protective clothing.
Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Reference to other sections
See Section 7 for information on safe handling.

in accordance with SANS

Printing date 18.03.2022

Trade name: Aktivator für Filtermembrane (CAT411,430)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

**Precautions for safe handling** Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Storage: Requirements to be met by storerooms and receptacles: Store in a cool location. Information about storage in one common storage facility: Not required. Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles. Storage class: 3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls or personal protection**

#### **Control parameters**

Ingredients with limit values that require monitoring at the workplace:

### CAS: 67-63-0 propan-2-ol

OEL Short-term value: 800 ppm Long-term value: 400 ppm

Additional information: The lists valid during the making were used as basis.

#### Exposure controls

Appropriate engineering controls *No further data; see item 7.* Individual protection measures, such as personal protective equipment (PPE)

### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

### **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Hand protection

Protective gloves

To avoid skin problems reduce the wearing of gloves to the required minimum. Only use chemical-protective gloves with CE-labelling of category III. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

### Material of gloves

Nitrile rubber, NBR The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be (Contd. on page 4)

– za –

Page 3/8

(Contd. of page 2)

in accordance with SANS

Printing date 18.03.2022

Trade name: Aktivator für Filtermembrane (CAT411,430)

checked prior to the application.

### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

### Eye or face protection

Tightly sealed goggles

Body protection: Protective work clothing

# **SECTION 9: Physical and chemical properties**

Information on basic physical and chemical prop	perties
General Information	
Physical state Colour:	Fluid
	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
نقطة الغليان أو نقطة الغليان الأولية ونطاق الغليان	82 °C
Flammability	Not applicable.
Upper or lower flammability or explosive limits	$2 \sqrt{2}$
Lower:	2 Vol % 12 Vol %
Upper:	
Flash point:	< 23 °C
Ignition temperature:	425 °C
Decomposition temperature:	Not determined.
pH Viceocity	Not determined.
Viscosity:	Not data main a d
Viscosity	Not determined.
Dynamic:	Not determined.
Solubility water:	Fully missible
Partition coefficient: n-octanol or water	Fully miscible. Not determined.
	43 hPa
Vapour pressure at 20 °C:	43 NPa
Vapour density + Relative density Density at 20 °C:	0.892 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
	Not determined.
Other information	
Appearance:	
Form:	Fluid
Important information on protection of health	
and environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	
Organic solvents:	50.0 %
Water:	50.0 %
Solids content:	0.0 %
Change in condition	
Evaporation rate	Not determined.
	(Contd. on p

Revision: 18.03.2022

(Contd. of page 3)

(Contd. on page 5)

– ZA –

in accordance with SANS Printing date 18.03.2022

Revision: 18.03.2022

(Contd. of page 4)

### Trade name: Aktivator für Filtermembrane (CAT411,430)

Information with regard to physical hazard classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Highly flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammable		
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

### **SECTION 10: Stability and reactivity**

Reactivity No further relevant information available. Chemical stability Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. Possibility of hazardous reactions No dangerous reactions known. Conditions to avoid No further relevant information available. Incompatible materials: No further relevant information available. Hazardous decomposition products: No dangerous decomposition products known.

# **SECTION 11: Toxicological information**

Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

### LD/LC50 values relevant for classification:

CAS: 67-63-0 propan-2-ol		
Oral	LD50	5,045 mg/kg (rat)
	LD50	5,045 mg/kg (rat) 12,800 mg/kg (rbt)
Inhalative	LC50/4 h	30 mg/l (rat)

Serious eye damage or irritation Causes serious eye irritation. Specific target organ toxicity – single exposure May cause drowsiness or dizziness. Information on other hazards

### endocrine disrupting potential

None of the ingredients is listed.

# **SECTION 12: Ecological information**

Toxicity

Aquatic toxicity: No further relevant information available. Persistence and degradability No further relevant information available. Bioaccumulative potential No further relevant information available. Mobility in soil No further relevant information available.

(Contd. on page 6)

ZA —

in accordance with SANS

Printing date 18.03.2022

Revision: 18.03.2022

### Trade name: Aktivator für Filtermembrane (CAT411,430)

Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable. Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties. Other adverse effects Additional ecological information: General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

# **SECTION 13: Disposal considerations**

Waste treatment methods Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

**Recommendation:** *Disposal must be made according to official regulations.* **Recommended cleansing agents:** *Water, if necessary together with cleansing agents.* 

# **SECTION 14: Transport information**

UN number IMDG, IATA UN proper shipping name ADR

UN1219

UN1219 ISOPROPANOL (ISOPROPYL ALCOHOL) solution ISOPROPANOL (ISOPROPYL ALCOHOL) solution Isopropanol (isopropyl alcohol) solution

IMDG IATA Transport hazard class(es)

ADR



Class	3 (F1) Flammable liquids.
Label	3

IMDG, IATA



Class	3 Flammable liquids.
Label	3
Packing group	
ADR, IMDG, IATA	11
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E,S-D
Stowage Category	В
Transport in bulk according to Annex II of	
MARPOL 73/78 and the IBC Code	Not applicable.

(Contd. on page 7)

\_\_\_\_\_ZA -

in accordance with SANS

Printing date 18.03.2022

Revision: 18.03.2022

Page 7/8

### Trade name: Aktivator für Filtermembrane (CAT411,430)

	(Contd. of page 6)
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL)
	SOLUTION, 3, II

### **SECTION 15: Regulatory information**

# Safety, health and environmental regulations specific for the product in question GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS). **Hazard pictograms** 



### Signal word Danger

Hazard-determining components of labelling: propan-2-ol Hazard statements Highly flammable liquid and vapour.

Causes serious eye irritation. May cause drowsiness or dizziness.

### **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed. Seveso category *P5c FLAMMABLE LIQUIDS* Qualifying quantity (tonnes) for the application of lower-tier requirements *5,000 t* Qualifying quantity (tonnes) for the application of upper-tier requirements *50,000 t* 

### National regulations:

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Department issuing SDS:** *PCC-TWR* **Contact:** *MSDS.pcc*@endress.com

(Contd. on page 8)

in accordance with SANS

Printing date 18.03.2022

Version 3 (replaces version 2)

Revision: 18.03.2022

### Trade name: Aktivator für Filtermembrane (CAT411,430)

(Contd. of page 7) Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 \* Data compared to the previous version altered.

ZA -