

TYPE APPROVAL CERTIFICATE

Certificate no.: **TAA00002B8**Revision No:

This is to ce	rtify:	
that the Panel Meter		
with type designation(s) RIA45		
issued to Endress+Hauser Wetzer GmbH+Co. KG Nesselwang, Germany		
is found to comply with DNV rules for classification – Ships, offshore units, and high speed and light craft		
Application:		
Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.		
Location classe Temperature Humidity Vibration EMC Enclosure	es: B B A B B (front) / A (rear)	
Issued at Hamburg on 2024-06-11		
This Certificate is valid until 2029-06-10 . for DNV		for DNV
DNV local unit: Augsburg		
Approval Engineer: Dariusz Lesniewski		

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251 Revision: 2023-09 www.dnv.com Page 1 of 2

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job ID: **262.1-030760-2** Certificate no.: **TAA00002B8**

Revision No: 1

Product description

The panel meter powers transmitters and processes analogue signals of transmitters.

The signals are monitored, evaluated, calculated, saved, separated, linked, converted and displayed.

Main technical data:

Power supply: 24V DC and 230V AC

Input: one or two universal inputs (measured variable: current, voltage, resistance, resistance

thermometer, thermocouples)

Output: one or two analog outputs, galvanically isolated. Connected sensors can be powered by the

integrated transmitter power supply system

Display: LC-display with 5-digit (display range -99999 to +99999)

Housing: plastic PC-GF10 Mounting: panel-mount

Degree of protection: front IP65, rear IP20

Ex-protection according to EC-type examination certificate no. PTB 08 ATEX 2036

Firmware version: 01.03.xx

Approval conditions

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV rules for classification of ships Pt.4 Ch.9 Control and monitoring systems.

Application/Limitation

Ex-version for only one input.

Type Approval documentation

Tests carried out

Applicable tests according to class guideline DNV-CG-0339, August 2021.

Marking of product

The products to be marked with:

- manufacturer name
- model name / serial number; power supply ratings

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- · Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE

Form code: TA 251 Revision: 2023-09 www.dnv.com Page 2 of 2