CRN Registration Liquiphant FTL31, FTL33, OFTL31, OFTL33

Registration No.: 0F16950.5C

Overview registered process connections

In Provinces:

British Columbia	Québec	Newfoundland & Labrador
Saskatchewan	New Brunswick	Yukon Territory
Manitoba	Nova Scotia	Northwest Territories
Ontario	Prince Edward Island	Nunavut
Alberta		

Design	Pressure components	Order code: 110	Remark / MAWP
Sanitary ferrule TriClamp ISO 2852	1” to 1- ½” (DN25-38) 2” (DN40-51)	3CJ, 3EJ	25 bar @-40°C...+150°C depending on clamp
Sanitary DIN11851 tube connection & slotted nut	DN25, DN32, DN40	1GJ, 1HJ, 1JJ	40 bar @ -40°C...+100°C 25 bar @ -40°C...+140°C
	DN50	accessory	25 bar @ -40°C...+140°C
SMS adapter connection & slotted nut	≤ 1-1/2”	accessory	25 bar @ -40°C...+150°C
E+H proprietary weld adapter, thread M24x1.5	≤ Ø 65 mm	accessory	
Varivent	F (DN25), N (DN32-DN162)	accessory	
Pipe thread ISO 228	G1/2”, G3/4”, G1”	WBJ, WCJ, WDJ	40 bar @ -40°C...+150°C
Pipe thread ISO 228 including welding boss	G3/4”, G1”	W5J, WSJ	40 bar @ -40°C...+100°C 25 bar @-40°C...+150°C
Thread ASME B1.1 ISO 13	M24x1.5	X2J	40 bar @ -40°C...+150°C
Thread NPT ASME B1.20.1-1983	NPT ½”, NPT ¾”, NPT 1”	VAJ, VBJ, VCJ	
Thread DIN EN 10226-1	R ½”, R ¾”, R1”	XBJ, XCJ, XDJ	
Flush mounted for welding neck 1”	G 1” aligned including welding boss Rd52 including welding boss	5ZJ	40 bar @ -40°C...+100°C 25 bar @ -40°C...+150°C