



Industrial Protecting Tube *omnigrad TA565*

Heavy duty - General purpose
From hexagonal bar stock
1" NPT threaded process connection



Straight



Conical

Description

TA565 is an industry standard thermowell, manufactured from hexagonal bar stock. The process connection is threaded. The thermowell stem shape can be straight or conical. The extension and the immersion lengths as well as the bar dimensions can be chosen according to process requirements. A wide choice of standard diameters and materials is available; other versions can be ordered according to specification. Different grades of surface finishing are also available.

Application

TA565 is designed for use with resistance and thermocouple thermometers mainly in heavy duty applications.

Technical data

Hexagonal bar	Wrench:	36 mm
	O.D.:	≤ 28 mm
	Standard bore diameter:	6.5 ÷ 10 mm
	Standard material:	AISI316 Ti, AISI316, AISI316 L

Connection to thermometer	Threaded:	1/2" NPT - female
----------------------------------	-----------	-------------------

Process connection	Threaded:	1" NPT
---------------------------	-----------	--------

Tip	Bottom shape:	straight or conical
	Bottom thickness:	6.35 mm

Surface	Finishing:	0.8 micron - standard 1.6 micron
----------------	------------	-------------------------------------

**Supplementary
Documentation**

- Technical Information Industrial Protecting Tubes (TI 138T/02/en)

Endress+Hauser
GmbH+Co.
Instruments International
P.O. Box 2222
D-79574 Weil am Rhein
Germany

Tel. (07621) 975-02
Tx 773926
Fax (07621) 975 345
<http://www.endress.com>
info@ii.endress.com

Endress + Hauser
The Power of Know How

